

TN28 Flow black polished



Größe Size	ET Offset	Nabenbohrung Center	Lochkreis PCD	Radlast Wheel load	Freigabe Approval
7,5 x 18"	45	72,6	5 x 108	950 kg	ABE
7,5 x 18"	47	66,5	5 x 112	950 kg	ABE
7,5 x 18"	53	71,1	5 x 118	1250 kg	ABE
7,5 x 18"	53	65,1	5 x 120	1050 kg	ABE
7,5 x 18"	53	78,1	5 x 130	1350 kg	ABE

hohe Radlast
high wheel load

TN28 Flow black painted



Größe Size	ET Offset	Nabenbohrung Center	Lochkreis PCD	Radlast Wheel load	Freigabe Approval
7,5 x 18"	45	72,6	5 x 108	950 kg	ABE
7,5 x 18"	47	66,5	5 x 112	950 kg	ABE
7,5 x 18"	53	71,1	5 x 118	1250 kg	ABE
7,5 x 18"	53	65,1	5 x 120	1050 kg	ABE
7,5 x 18"	53	78,1	5 x 130	1350 kg	ABE

hohe Radlast
high wheel load

Winterfest
Winterproof



Extrem leicht
Superlight
8,37 kg

Winterfest
Winterproof

TN29 Superlight bronze

Größe Size	ET Offset	Nabenbohrung Center	Lochkreis PCD	Freigabe Approval
8,5 x 19"	45	72,6	5 x 112	ABE
8,5 x 19"	40	72,6	5 x 114,3	ABE
8,5 x 19"	45	72,6	5 x 114,3	ABE



Extrem leicht
Superlight
8,37 kg

Winterfest
Winterproof

TN29 Superlight black painted

Größe Size	ET Offset	Nabenbohrung Center	Lochkreis PCD	Freigabe Approval
8,5 x 19"	45	72,6	5 x 112	ABE
8,5 x 19"	40	72,6	5 x 114,3	ABE
8,5 x 19"	45	72,6	5 x 114,3	ABE



Extrem leicht
Superlight
8,37 kg

Winterfest
Winterproof

TN29 Superlight hypersilver

Größe Size	ET Offset	Nabenbohrung Center	Lochkreis PCD	Freigabe Approval
8,5 x 19"	45	72,6	5 x 112	ABE
8,5 x 19"	45	72,6	5 x 114,3	ABE